

Application: Plastifloor® SL Filler serves as additive for Plastifloor® Resins.

Characteristics: Plastifloor® SL Filler consists of crystal quartz sands. They are characterised by their SiO₂ – content and are free from humidic substances.

Packaging: 55.11 lb special paper bags

Note: Packed products are subject to normal aging and should not be stored longer than 6 months. Disposal recommendations may be taken from our Material Safety Data Sheet.

Grain size distribution:

grain size [mesh]	share [weight%]
> 35	< 0,5
150 - 35	app. 50
> 150	app. 50

Data concerning our products and devices as well as concerning our data and procedures are based on an extensive research work and an application technology experience. We obtain these results, with which we do not take over adhesion going beyond the respective single contract, in word and writing after best knowledge, reserve ourselves we however technical changes in the course of the product development. Beyond that our application technology service stands when desired for large consultation as well as for co-operation with the solution manufacturing and application technology problems for order. That does not relieve the user however to examine our data and recommendations before their use responsible for the own use. That applies - particularly for deliveries to foreign markets - also regarding the keeping of patent rights third as well as for applications and procedures, which are not expressly in writing indicated by us. The case of loss our adhesion is limited to indemnifications of same extent, as they plan our general terms of delivery and sales with lack of quality.

12/02/2019

1 / 1