

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1 Product identifier

Trade name: **PLASTIPUR® 370 Component A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Polyaspartic Resin.

Uses advised against: not determined.

1.3 Details of the supplier of the safety data sheet

Supplier: **Plasti-Chemie Produktionsgesellschaft mbH**
Address: Falgardring 1
D-08223 Falkenstein
Germany

Telephone/Fax number: +49 3745/74432-0 / +49 3745/74432-27

E-mail address for a competent person responsible of sds: volkmar.lull@plasti-chemie.de

Further information provided by: Mr. Volkmar Lull, +49 3745/74432-0

1.4 Emergency telephone number

Chemtrec: 1-800-424-9300 for US

+1 703-527-3887 outside US

Europa 112

Österreich +43 1 406 43 43

Belgien Poison center (BE): +32 70 245 245

Dänemark Poison Control Hotline (DK): +45 82 12 12 12

Finnland Poison Information Centre (FI): +358 9 471 977

Frankreich ORFILA (FR): + 01 45 42 59 59

Deutschland Giftnotruf Berlin, Tel. 030 30686 790

Poison Center Nord: +49 551 19240 (24h erreichbar, Deutsch und Englisch)

Poison Information Centre Erfurt: +49 361 730730 (Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen c/o HELIOS Klinikum Erfurt Nordhäuser Straße 74, 99089 Erfurt)

Irland National Poisons Information Centre (IE): +353 1 8379964

Island +354 543 2222

Italien Poison Center, Milan (IT): +39 02 6610 1029

Luxemburg 112

Niederlande National Poisons Information Center (NL): +31 30 274 88 88 (NB: this service is only available to health professionals)

Norwegen Poisons Information (NO): + 47 22 591300

Portugal Poison Information Center (PT): +351 21 330 3284

Spanien Poison Information Service (ES): +34 91 562 04 20

Schweden Poisons Information Center (SV): +46 8 33 12 31

Schweiz Poison Center: Tel 145; +41 44 251 51 51

Großbritannien NHS Direct (UK): +44 (0) 845 46 47; 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to regulation (EG) 1272/2008/WE

Skin Sens. 1 H317, Eye Sens. 1B H317, Aquatic Chronic 3 H412

May cause an allergic skin reaction. Harmful to aquatic life with long-lasting effects.

2.2 Label elements

This substance is graded and classified according to (EG) No. 1272/2008 [CLP].

Hazard symbols and signal words

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG



Warning

Product identifier

Contains: Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethylester
Aspartic Ester

Hazard statements

H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long-lasting effects.

Precaution statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash before reuse.

2.3 Other hazards

The components of this mixture do not meet the criteria for PBT or vPvB in accordance of Annex XIII of REACH.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance

Not applicable.

3.2 Mixture

CAS: 136210-30-5 Index-Nr.: 607-521-00-8 REACH Reg. Nr.: 01-0000017556-64-0000	<u>Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:</u> Classification acc. to 1272/2008/WE: Skin Sens. 1 H317, Aquatic Chronic 3 H412	60 - 80 %
CAS: 152637-10-0	<u>Aspartic Ester:</u> Classification acc. to 1272/2008/WE: Skin Sens. 1B H317, Aquatic Chronic 3 H412	20 - 30 %
CAS: 1318-02-1 EINECS: 215-283-8 REACH Reg. Nr.: 01-211942034-49-XXXX	<u>Zeolite (crystalline aluminosilicate):</u> Classification acc. to 1272/2008/WE: -	2,5 - 3,5 %
	<u>Deaerating Polymer mixture:</u> Classification acc. to 1272/2008/WE: -	1,5 - 2,5 %
CAS: 27306-78-1 Index-Nr.: 608-078-3	<u>Polyether-modified Trisiloxane:</u> Classification acc. to 1272/2008/WE: Acute Tox. 4 H302, Eye Irrit. 2 H319, Acute Tox. 4 H332, Aquatic Chronic 2 H411	0,1 - 0,4 %

Additional information: For the wording of the hazard statements refer to section 16.

ABSCHNITT 4: FIRST AID MEASUREMENTS

4.1 Description of first aid measurements

General information: Immediately remove all contaminated clothing.

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

Inhalation:	Take affected persons out into fresh air. In case of breathing difficulties seek medical attention.
Skin contact:	Wash immediately with soap and water and rinse thoroughly. Consult doctor if symptoms persist.
Eye contact:	Wash the eye with the eyelid open for several minutes under running water. Protect unharmed eye. Consult doctor if symptoms persist.
Ingestion:	Do not induce vomiting. Immediately consult doctor.
4.2 Most important symptoms and effects, both acute and delayed	Notes to physician: Elementary aid, decontamination, symptomatic treatment.
4.3 Indication of any immediate medical attention and special treatment	No further relevant information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguish media	<u>Suitable extinguish media:</u> Carbon dioxide (CO ₂) Extinguishing powder, foam. Fight larger fires with water spray. <u>Unsuitable extinguish media:</u> Water jet – fire spread risk.
5.2 Special hazards arising from the substance or mixture	In case of fire, it can be released: Carbon Monoxide (CO), Carbon Dioxide (CO ₂), Nitrogen Oxides (NO _x), Isocyanate vapours, traces of hydrogen cyanide (HCN). Do not inhale explosion and combustion gases.
5.3 Advise for firefighters	<u>Special protective equipment:</u> Self-contained breathing apparatus, chemical resistant protective clothing <u>Additional information:</u> Do not allow contaminated firefighting water to get into ground/sewers/ground water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Do not breathe fumes. Ensure adequate ventilation. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions	Do not allow product to reach sewage system, water bodies or ground/soil.
6.3 Methods and material for containment and cleaning up	Collect with chemical binders, if necessary dry sand and store in closed containers. Ensure adequate ventilation.
6.4 Reference to other sections	<u>Disposal:</u> Section 13. <u>Personal protective equipment:</u> Section 8 <u>Safe Handling:</u> Section 7.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	Ensure good ventilation/exhaustion at the workplace. Air extraction is required for spray processing. Wash hands before breaks and at the end of work. Use skin protection ointment. Immediately remove all contaminated clothing. Avoid contact with skin or eyes.
7.2 Conditions for safe storage, including any incompatibilities	<u>Notes on fire and explosion protection:</u> No special actions required. <u>Requirements for storage rooms and containers:</u> Store in a cool, well ventilated place. <u>Storage compatibility:</u> Keep away from foodstuffs, beverages and food.

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

Additional information: Keep container tightly sealed and store in a cool location.
Storage class: 10

7.3 Specific end use(s)
No further relevant information available.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Components with community workplace exposure limits:

DNEL

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

DNEL	Oral	Inhalation	Dermal
Worker Long-term systemic Effects	4 mg/kg	28 mg/m ³	4 mg /kg

27306-78-1 Polyether-modified Trisiloxane:

DNEL	Oral	Inhalation	Dermal
Worker Long-term systemic Effects	-	53,4 mg/m ³	333 mg /kg
Consumer Long-term systemic Effects	0,27 mg/kg	13,3 mg/m ³	167 mg/kg

PNEC

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

PNEC Freshwater	0,00013 mg/L
PNEC Marinewater	0,000013mg/L
PNEC Freshwater sed	0,21 mg/kg (Dry weight)
PNEC Marinewater sed	0,02 mg/kg (Dry weight)
PNEC Soil	0,1 mg/kg (Dry weight)
PNEC Wastewater treatment plant	31,1 mg/L
PNEC Oral	66,67 mg/kg (Food)

27306-78-1 Polyether-modified Trisiloxane:

PNEC Freshwater	0,002 mg/L
PNEC Marinewater	0,0002mg/L
PNEC Freshwater sed	1,7 mg/kg (Dry weight)
PNEC Marinewater sed	0,17 mg/kg (Dry weight)
PNEC Soil	0,083 mg/kg (Dry weight)
PNEC Wastewater treatment plant	10 mg/L
PNEC Oral	67 mg/kg (Food)

8.2 Exposure controls

General safety and hygiene measures:

Keep away from foodstuff, beverages and food.

Immediately remove contaminated clothing.

Wash hand thoroughly before breaks and at the end of work.

Avoid contact with skin and eyes.

Respiratory protection:

In case of insufficient ventilation at workplace or spray processing respiratory protection is required.

In case of hypersensitivity to the respiratory tract and the skin (asthma, chronic bronchitis, chronic skin disorders) the handling of the product is not recommended.



Combination-filter Type A-X (Carbon filter) and Type P (Particle filter)

Hand protection:

Only use chemical protective gloves with CE labelling of Category III according to EN 374.

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG



Selection of the glove material on consideration of the permeation times, rates of diffusion and the degradation.

Glove material:

The selection of an adequate glove not only depends on the material, but also from different other quality characteristics and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Multi-layer-glove – PE/EVAL/PE.

Penetration time of glove material:

The exact break through time is to be learned from the manufacturer and must be maintained. The break through time is dependent of the activity and usage time

Eye protection:



Tightly sealed goggles

Body protection:

Protective clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:

Physical state:

Liquid

Colour:

Yellow, milky

Odour:

Characteristic

Odour threshold:

Not determined.

Safety relevant basic data:

Parameters

Density:

1,07

Unit
g/cm³

Remark

Bulk density:

not determined

pH value:

not determined

Melting point/Melting range:

app. -2

°C

Aspartic acid

Boiling point/Boiling range:

not determined

Flash point:

app. 100

°C

Aspartic acid

Flammability (solid/gaseous)

not applicable

Explosion dangerousness:

not explosive¹

lower Explosion limit:

not determined

upper Explosion limit:

not determined

Ignition temperature:

375

°C

Aspartic acid

Decomposition temperature:

234

°C

Aspartic acid

Oxidising potential:

not determined

Vapour pressure:

not determined

Rate of vaporization:

not determined

Water solubility:

not miscible

Liposolubilty:

not determined

Soluble in:

not determined

Distribution coefficient:

not determined

n-Octanol/Water:

not determined

Viscosity:

app. 350

mPas

dynamic ²

Solvent separation test:

not determined

Solvent content:

not determined

¹ Formation of explosive vapor / air mixtures is possible

² DIN 53019 20°C

9.2 Other information

No further relevant information available.

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity**
No further relevant information available.
- 10.2 Chemical stability**
No further relevant information available.
- 10.3 Possible hazardous reactions**
No hazardous reactions when stored and handled correctly.
- 10.4 Conditions to avoid**
No further relevant information available.
- 10.5 Incompatible materials**
No further relevant information available.
- 10.6 Hazardous decomposition products**
No hazardous decomposition products when stored and handled correctly.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute Toxicity:

Relevant LD/LC50 Values:

136210-30-5 Aspartic Acid, N,N'-(methylen-di-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:	Oral Dermal Inhalation	LD50 (Rat) > 2000 mg/kg (OECD 423) LD50 (Rat) > 2000 mg/kg LC50 (Rat) > 4,224 mg/L / 4h (OECD 403)
152637-10-0 Aspartic Ester:	Oral Dermal Inhalation	LD50 (Rat) > 2000 mg/kg (OECD 423) LD50 (Rat) > 2000 mg/kg LC50 (Rat) > 4,224 mg/L / 4h (OECD 403)

Irritation to the skin:

May cause an allergic skin reaction.

Serious eye damage/irritation:

No irritant effect.

Respiratory or skin sensitisation:

Sensitisation possible through skin contact.

Aspiration hazard:

Based on available data the classification criteria are not met.

CMR effects:

Carcinogenicity

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Other information:

Specific Target Organ Toxicity:

Single exposure

Based on available data the classification criteria are not met.

Repeated exposure

Based on available data the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

Aquatic Toxicity:

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

LC50 (Danio rerio): 66 mg/L / 96 h (OECD 203)

EC50 (Daphnia magna): 88,6 mg/L / 48 h (67/548/EWG; V, C.2.)

ErC50 (Scenedemus subspicatus): 113 mg/L / 72 h (67/548/EWG; V, C.3.)

EC50 (Activated sludge): 3110 mg/L / 3 h (EG-RL 88/302/EEC)

152637-10-0 Aspartic Ester:

LC50 (Danio rerio): 66 mg/L / 96 h (OECD 203)

EC50 (Daphnia magna): >100 mg/L / 48 h (OECD 202)

ErC50 (Scenedemus subspicatus): >100 mg/L / 72 h (OECD 201)

EC50 (Activated sludge): >1000 mg/L / 3 h (OECD 209)

12.2 Persistence and degradability

Biodegradability:

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

OECD 301 F Biodegradation: 13%, 23d; Not easily degradable

OECD 302 C Biodegradation: 0%, 23d; Not potentially degradable

152637-10-0 Aspartic Ester:

OECD 301 D Biodegradation: 23%, 23d; Not easily degradable

OECD 302 C Biodegradation: 0%, 23d; Not potentially degradable

Stability in water:

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

OECD 111 Half-life time: 655 h at 25 °C (pH 4)

Half-life time: 25,4 h at 25 °C (pH 7)

Half-life time: 16,8 h at 25 °C (pH 9)

152637-10-0 Aspartic Ester:

OECD 111 Half-life time: 655 h at 25 °C (pH 4)

Half-life time: 25,4 h at 25 °C (pH 7)

Half-life time: 16,8 h at 25 °C (pH 9)

Volatility (Henry's law constant):

136210-30-5 Aspartic Acid, N,N'-(methylendi-4,1-cyclohexandiyl)bis-1,1',4,4'-tetraethyl ester:

Calculated value = 0.01 Pa * m³ / mol

152637-10-0 Aspartic Ester:

Calculated value = 0.01 Pa * m³ / mol

The product is classified as biologically not readily degradable, with low degradability potential. It is classified as non-volatile from water.

12.3 Bioaccumulative potential

Enrichment in water organisms is not to be expected.

12.4 Mobility in Soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

The PBT/vPvB criteria of REACH are not applicable for this substance.

12.6 Other adverse effects

Ecotoxic effects: The product is classified as low water hazard.

General information: Do not allow product to reach ground water, sewers or into the sewage system.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods for the product:

Dispose according to national regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue:

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 02 00 Wastes from MFSU of other coatings (including ceramic materials)

08 02 99 Wastes NOS

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

Disposal methods for used packing:

Perform recycling in accordance with applicable regulations.

Only fully emptied packaging is recyclable.

SECTION 14: TRANSPORT INFORMATION

14.1 UN-Number

Not applicable.

14.2 UN proper shipping name

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing group

Not applicable.

14.5 Environmental hazards

Not applicable.

14.6 Special precautions for user

No hazardous material. Protect from moisture. Keep away from food, beverages, acids and alkalis

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific to the substance or mixture

Directive 2012/18/EU

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

Regulation (EU) 453/2010

National regulations:

Other regulations, limitations and prohibitive regulations

Water hazardous class:

1 (self-classification) slightly water endangering

Substances of very high concern (SVHC) according to REACH, Article 57:

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: OTHER INFORMATION

Additional details:

Classification was made based on the data on the content of hazardous substances using the calculation method based on the guidelines of regulation 1272/2008/EC (CLP).

Relevant Phrases:

H302 Harmful if swallowed

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled

H411 Toxic to aquatic life with long-lasting effects.

SAFETY DATA SHEET

[in accordance with the regulation no. 1907/2006/EG (REACH)]

Date of issue: 28.04.2018

Version: 1/ENG

H412 Harmful to aquatic life with long-lasting effects.

Safety Data Sheet issuing person:

Pascal Konrad

Safety Data Sheet issued on:

10.11.2016