

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PLASTIFLOOR® 526

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Coatings.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Plasti Chemie Produktionsgesellschaft mbH	
Street:	Falgardring 1	
Place:	D-08223 Falkenstein	
Telephone:	+49 (0)3745/74432-0	Telefax: +49 (0)3745/74432-27
e-mail:	volkmar.lull@plasti-chemie.de	
Contact person:	Hr. Volkmar Lull	Telephone: +49 (0)3745/74432-0
Internet:	www.plasti-chemie.de	
Responsible Department:	volkmar.lull@plasti-chemie.de	

1.4. Emergency telephone number:

Chemtrec: 1-800-424-9300 for US
+1 703-527-3887 outside US
NHS Direct (UK): +44 (0) 845 46 47; 111

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

Tetramethylene dimethacrylate

2-ethylhexyl acrylate

2,2'-[(4-methylphenyl)imino]bisethanol

2,2-bis[[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)]

2-(2H-benzotriazol-2-yl)-p-cresol

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl]-(4-methylphenyl)amino]ethanol and 2,2'-

[(4-methylphenyl)imino]diethanol

Ethylene di(S-thioacetate)

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 2 of 17

Pictograms:

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	60 - < 65 %
	201-297-1	607-035-00-6
		01-2119452498-28
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
2082-81-7	Tetramethylene dimethacrylate	5 - < 7 %
	218-218-1	01-2119967415-30
	Skin Sens. 1B; H317	
103-11-7	2-ethylhexyl acrylate	3 - < 5 %
	203-080-7	607-107-00-7
		01-2119453158-37
	Skin Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H315 H317 H335 H412	
3077-12-1	2,2'-[[4-methylphenyl]imino]bisethanol	0.3 - < 0.5 %
	221-359-1	01-2120791684-40
	Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H318 H317 H412	
10193-99-4	2,2-bis[[[mercaptoacetyl]oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)	0.1 - < 0.2 %
	233-482-8	
	Acute Tox. 4, Skin Sens. 1A; H302 H317	
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	0.1 - < 0.2 %
	219-470-5	01-2119583811-34
	Skin Sens. 1B, Aquatic Chronic 1; H317 H410	
-	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol	0.1 - < 0.2 %

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 3 of 17

	911-490-9		01-2119979579-10	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412			
123-81-9	Ethylene di(S-thioacetate)			< 0.1 %
	204-653-4			
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 2; H332 H312 H302 H315 H319 H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	60 - < 65 %
		inhalation: LC50 = 29,8 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = >5000 mg/kg	
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 7 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = (10,066) mg/kg	
103-11-7	203-080-7	2-ethylhexyl acrylate	3 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = 4435 mg/kg	
3077-12-1	221-359-1	2,2'-[[4-methylphenyl]imino]bisethanol	0.3 - < 0.5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 959 mg/kg	
10193-99-4	233-482-8	2,2-bis[[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)	0.1 - < 0.2 %
		oral: ATE = 500 mg/kg	
2440-22-4	219-470-5	2-(2H-benzotriazol-2-yl)-p-cresol	0.1 - < 0.2 %
		dermal: LD50 = > 1000 mg/kg; oral: LD50 = 10000 mg/kg	
-	911-490-9	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol	0.1 - < 0.2 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 619 mg/kg	
123-81-9	204-653-4	Ethylene di(S-thioacetate)	< 0.1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg	

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 4 of 17

After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area.
Wear personal protection equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 5 of 17

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.
Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.
Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.
Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.
Keep away from food, drink and animal feedingstuffs.
Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.
Ensure adequate ventilation of the storage area.
Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.
Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.
Protect against: UV-radiation/sunlight. heat. Humidity frost.
storage temperature: 5-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 6 of 17

Worker DNEL, long-term	inhalation	systemic	208 mg/m ³
Worker DNEL, long-term	dermal	systemic	13.67 mg/kg bw/day
Worker DNEL, long-term	dermal	local	1.5 mg/cm ²
Worker DNEL, acute	dermal	local	1.5 mg/cm ²
Worker DNEL, long-term	inhalation	local	208 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	74.3 mg/m ³
Consumer DNEL, long-term	inhalation	local	104 mg/m ³
Consumer DNEL, long-term	dermal	systemic	8.2 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	1.5 mg/cm ²
Consumer DNEL, acute	dermal	local	1.5 mg/cm ²
2082-81-7	Tetramethylene dimethacrylate		
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m ³
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m ³
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol		
Worker DNEL, long-term	inhalation	systemic	3,29 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,47 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,58 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,17 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,16 mg/kg bw/day
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol		
Worker DNEL, long-term	inhalation	systemic	1 mg/m ³
Worker DNEL, acute	inhalation	systemic	1 mg/m ³
Worker DNEL, acute	inhalation	local	1 mg/m ³
Worker DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	1,2 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1,2 mg/kg bw/day
-	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl)imino]diethanol		
Worker DNEL, long-term	inhalation	systemic	9,8 mg/m ³
Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day

PNEC values

CAS No	Substance	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 7 of 17

Freshwater	0.94 mg/l
Marine water	0.94 mg/l
Freshwater sediment	5.74 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	1.47 mg/kg
2082-81-7	Tetramethylene dimethacrylate
Freshwater	0,043 mg/l
Freshwater (intermittent releases)	0,098 mg/l
Marine water	0,004 mg/l
Freshwater sediment	3,12 mg/kg
Marine sediment	0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)	2 mg/l
Soil	0,573 mg/kg
3077-12-1	2,2'-[[4-methylphenyl]imino]bisethanol
Freshwater	0,026 mg/l
Freshwater (intermittent releases)	0,26 mg/l
Marine water	0,003 mg/l
Freshwater sediment	0,121 mg/kg
Marine sediment	0,012 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,009 mg/kg
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol
Freshwater	0 mg/l
Freshwater (intermittent releases)	0,001 mg/l
Marine water	0 mg/l
Freshwater sediment	0,136 mg/kg
Marine sediment	0,014 mg/kg
Micro-organisms in sewage treatment plants (STP)	1 mg/l
Soil	100 mg/kg
-	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl][(4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol
Freshwater	0,048 mg/l
Freshwater (intermittent releases)	0,48 mg/l
Marine water	0,005 mg/l
Freshwater sediment	1,2 mg/kg
Marine sediment	0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,21 mg/kg

8.2. Exposure controls


Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 8 of 17

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Skin protection

Wear fire/flamm resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	violet
Odour:	characteristic

Test method**Changes in the physical state**

Melting point/freezing point: not applicable

Boiling point or initial boiling point and boiling range: not determined

Flash point: 10 (MMA) °C DIN 51755

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: not determined

Upper explosion limits: not determined

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 9 of 17

Auto-ignition temperature: not determined

Decomposition temperature: not determined

Oxidizing properties

none.

pH-Value: not determined

Viscosity / dynamic:
(at 40 °C) not determinedViscosity / kinematic:
(at 20 °C) not determined

Flow time: not determined

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure:
(at 20 °C) 38,7 (MMA) hPaDensity (at 20 °C): 1 g/cm³

Relative vapour density: not determined

9.2. Other information**Other safety characteristics**

Solvent separation test: not determined

Solvent content: not determined

Solid content: not determined

Evaporation rate: not determined

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactionsReacts with : Amines
Refer to chapter 10.5.**10.4. Conditions to avoid**Keep away from heat. Danger of explosion!
In use may form flammable/explosive vapour-air mixture.
Heating causes rise in pressure with risk of bursting.**10.5. Incompatible materials**

Materials to avoid: Oxidizing agents, strong. Strong acid.

10.6. Hazardous decomposition productsDoes not decompose when used for intended uses.
Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).**SECTION 11: Toxicological information**

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 10 of 17

11.1. Information on hazard classes as defined in GB CLP Regulation
Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate				
	oral	LD50 mg/kg >5000	Rat	ECHA Dossier	WoE
	dermal	LD50 mg/kg > 5000	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) aerosol	LC50 29,8 mg/l	Rat	ECHA Dossier	
2082-81-7	Tetramethylene dimethacrylate				
	oral	LD50 mg/kg (10,066)	Rat	Study report (1978)	OECD Guideline 401
	dermal	LD50 mg/kg > 3000	Rabbit	Kirk-Othmer, Encyclopedia of chemical te	
103-11-7	2-ethylhexyl acrylate				
	oral	LD50 mg/kg 4435	Rat	ECHA Dossier	
	dermal	LD50 mg/kg >2000	Rabbit	ECHA Dossier	
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol				
	oral	LD50 mg/kg 959	Rat	Study report (1981)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rat	Study report (2013)	OECD Guideline 402
10193-99-4	2,2-bis[[mercaptoacetyl]oxy]methyl]-1,3-propanediyl bis(mercaptoacetate)				
	oral	ATE mg/kg 500			
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol				
	oral	LD50 mg/kg 10000	Rat	Study report (1978)	OECD Guideline 423
	dermal	LD50 mg/kg > 1000	Rat	Study report (1972)	OECD Guideline 402
-	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol				
	oral	LD50 mg/kg 619	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rat	Study report (2013)	OECD Guideline 402
123-81-9	Ethylene di(S-thioacetate)				
	oral	ATE mg/kg 500			
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 11 of 17

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; Tetramethylene dimethacrylate; 2-ethylhexyl acrylate; 2,2'-[(4-methylphenyl)imino]bisethanol; 2,2-bis[[(mercaptoacetyl)oxy]methyl]-1,3-propanediyl bis(mercaptoacetate); 2-(2H-benzotriazol-2-yl)-p-cresol; Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[(4-methylphenyl)imino]diethanol; Ethylene di(S-thioacetate))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards
Endocrine disrupting properties

No data available.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	Acute fish toxicity	LC50 >79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 >110 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna	ECHA Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 9,4 mg/l	35 d	Brachydanio rerio	ECHA Dossier	
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna	ECHA Dossier	OECD Guideline 211
	Acute bacteria toxicity	(100 mg/l)		activated sludge	ECHA Dossier	OECD 301C
2082-81-7	Tetramethylene dimethacrylate					
	Acute algae toxicity	ErC50 (4,97) mg/l	72 h	Desmodesmus subspicatus	REACH Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC 5,09 mg/l	21 d	Daphnia magna	REACH Dossier	OECD Guideline 211
103-11-7	2-ethylhexyl acrylate					
	Acute fish toxicity	LC50 1,81 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier	
	Acute algae toxicity	ErC50 1,71 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50 1,3 mg/l	48 h	Daphnia magna	ECHA Dossier	

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 12 of 17

3077-12-1 2,2'-[(4-methylphenyl)imino]bisethanol						
	Acute fish toxicity	LC50 mg/l	> 100	96 h		REACH Registration Dossier
	Acute algae toxicity	ErC50 mg/l	> 100	72 h		REACH Registration Dossier
	Acute crustacea toxicity	EC50	(48) mg/l	48 h		REACH Registration Dossier
	Acute bacteria toxicity		(> 1000 mg/l)	3 h		REACH Registration Dossier
2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol						
	Acute fish toxicity	LC50 mg/l	> 0,17	96 h	Oncorhynchus mykiss	Study report (2004) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 0,0822	72 h	Pseudokirchneriella subcapitata	Study report (2018) OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	0,013	21 d	Daphnia magna	Study report (2011) OECD Guideline 211
	Acute bacteria toxicity		(> 100 mg/l)	3 h	Activated sludge	Study report (1988) OECD Guideline 209
- Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl)imino]diethanol						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Cyprinus carpio	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50	(48) mg/l	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Acute bacteria toxicity		(> 1000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier OECD Guideline 209

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
103-11-7	2-ethylhexyl acrylate			
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	>80%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,32
2082-81-7	Tetramethylene dimethacrylate	3,1

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 13 of 17

103-11-7	2-ethylhexyl acrylate	4,64 (25°C)
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol	2
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	15900
-	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol	2

BCF

CAS No	Chemical name	BCF	Species	Source
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	1456	Oncorhynchus mykiss	REACH Registration D

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - used product

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1866

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 14 of 17

14.2. UN proper shipping name: RESIN SOLUTION**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Special Provisions: 640D

Limited quantity: 5 L

Excepted quantity: E2

Transport category: 2

Hazard No: 33

Tunnel restriction code: D/E

Inland waterways transport (ADN)**14.1. UN number:** UN 1866**14.2. UN proper shipping name:** Resin solution**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Special Provisions: 640D

Limited quantity: 5 L

Excepted quantity: E2

Marine transport (IMDG)**14.1. UN number:** UN 1866**14.2. UN proper shipping name:** RESIN SOLUTION**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Marine pollutant: NO

Special Provisions: -

Limited quantity: 5 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1866**14.2. UN proper shipping name:** RESIN SOLUTION**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 15 of 17



Special Provisions:	A3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC):	not determined
2004/42/EC (VOC):	not determined
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)
The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
Tetramethylene dimethacrylate
2-ethylhexyl acrylate

SECTION 16: Other information**Changes**

Rev. 1.00; Initial release: 25.05.2021

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 16 of 17

CLP: Classification, Labelling and Packaging of substances and mixtures
 DNEL: Derived No Effect Level
 d: day(s)
 EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 ECHA: European Chemicals Agency
 EWC: European Waste Catalogue
 IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
 h: hour
 LOAEL: Lowest observed adverse effect level
 LOAEC: Lowest observed adverse effect concentration
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NOAEL: No observed adverse effect level
 NOAEC: No observed adverse effect concentration
 NLP: No-Longer Polymers
 N/A: not applicable
 OECD: Organisation for Economic Co-operation and Development
 PNEC: predicted no effect concentration
 PBT: Persistent bioaccumulative toxic
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 REACH: Registration, Evaluation, Authorisation of Chemicals
 SVHC: substance of very high concern
 TRGS: Technische Regeln für Gefahrstoffe
 UN: United Nations
 VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

PLASTIFLOOR® 526

Revision date: 26.05.2021

Product code:

Page 17 of 17

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)